

- Female M8
- straight



General attributes

Additional features	Drag chain compatible
Approvals / Conformity	cULus LISTED
Cable jacket color	gray
Enclosure Type per IEC 60529	IP67
Function indicator (PIN 4)	No
Power indicator	No
Trademark	GLOBAL

Electrical attributes

Operating voltage UB max. AC [V]	60.0 V
Operating voltage UB max. DC [V]	60.0 V
Rated current (40°C)	4.0 A
Switching function	Normally open (NO)
Switching output	No



Mechanical attributes

Acceleration max. (drag chain)	5 m/s ²
Ambient temp. max. (fixed)	105 °C (UL 80 °C)
Ambient temp. max. (moving)	105 °C (UL 80 °C)
Ambient temp. max. (drag chain)	60 °C
Ambient temp. min. (fixed)	-40 °C
Ambient temp. min. (moving)	-5 °C
Ambient temp. min. (drag chain)	-5 °C
Bending cycles	> 2 Mio.

Bending radius fixed cable	min. 5 x D
Bending radius tensioned cable	min. 10 x D
Cable diameter D	4.5 +/- 0.15 mm
Cable jacket material	PVC
Cable length L [m]	2.00 m
Conductor cross-section	0.34 mm ²
Connector configuration	straight
Connector type	M08x1
Connector type (Header I)	Female M8
Contact material	CuSn
Cover nut material	GD-Zn
Drag chain compatible	Yes
Grip material	PUR
Number of conductors	3
Number of female/male pins	3
Permiss.horizon. traverse dist	at 5 m/sec ² 5 m
Permiss.vert. traverse dist	at 5 m/sec ² 2 m
System	molded
Tightening torque pigtail	0.4 Nm
Traverse speed max(drag chain)	at 5 m horiz. travel 200 m/min

Additional text

Cable structure according to UL-AWM Style 2517
 Enclosure type accord. to IEC 60529, when threaded together with the appropriate counterpart.



PIN 1: brown
 PIN 3: blue
 PIN 4: black