

- Female M8
- 90°angle



General attributes

Additional features	Drag chain compatible
Approvals / Conformity	cULus LISTED
Cable jacket color	gray
Enclosure Type per IEC 60529	IP67
Function indicator (PIN 2)	No
Function indicator (PIN 4)	No
Power indicator	No
Trademark	GLOBAL

Electrical attributes

Operating voltage UB max. AC [V]	30.0 V
Operating voltage UB max. DC [V]	30.0 V
Rated current (40°C)	4.0 A
Switching function	Complementary (NO/NC)
Switching output	No

Mechanical attributes


Acceleration max. (drag chain)	5 m/s ²
Ambient temp. max. (fixed)	105 °C (UL 80 °C)
Ambient temp. max. (moving)	105 °C (UL 80 °C)
Ambient temp. max.(drag chain)	60 °C
Ambient temp. min. (fixed)	-40 °C
Ambient temp. min. (moving)	-5 °C
Ambient temp. min.(drag chain)	-5 °C
Bending cycles	> 2 Mio.

Bending radius fixed cable	min. 5 x D
Bending radius tensioned cable	min. 10 x D
Cable diameter D	4.8 +/- 0.15 mm
Cable jacket material	PVC
Cable length L [m]	2.00 m
Conductor cross-section	0.34 mm ²
Connector configuration	90°angle
Connector type	M08x1
Connector type (Header I)	Female M8
Contact material	CuSn
Cover nut material	GD-Zn
Drag chain compatible	Yes
Grip material	PUR
Number of conductors	4
Number of female/male pins	4
Permiss.horizon. traverse dist	at 5 m/sec ² 5 m
Permiss.vert. traverse dist	at 5 m/sec ² 2 m
System	molded
Tightening torque pigtail	0.4 Nm
Traverse speed max(drag chain)	at 5 m horiz. travel 200 m/min

Additional text

Enclosure type accord. to IEC 60529, when threaded together with the appropriate counterpart.
 Cable structure according to UL-AWM Style 2517

- 1 _____
- 2 _____
- 3 _____
- 4 _____



PIN 1: brown
 PIN 2: white
 PIN 3: blue
 PIN 4: black