

Field-Attachable Connectors BCC M343-0000-10-000-34X325-000 Ordercode: BCC06YY

BALLUFF





Display/Operation		
Power indicator	no	
Electrical connection		
Cable diameter D	3.55 mm	
Connector 01, version	angled	
Number of pins	3	
System	Can be fabricated	
Electrical data		
Operating voltage Ub	60 VDC / 60 VAC	
Rated current (40 °C)	4.0 A	
Environmental conditions		
	-2585 °C	
Ambient temperature	-2565 C	

IP rating per IEC 60529	IP67
Material	
Material contact carrier	PA
Material contacts	Brass
Material cover nut	Brass
Material grip	PBT
Mechanical data	
Connection cross-section	0.140.34 mm²
Tightening torque pigtail	0.4 Nm
Type of wire mounting	Solder connections
Remarks	
Enclosure rating per IEC 60529, only mating piece.	y in screwed state with the associated



Internet Balluff Germany Balluff USA Balluff China www.balluff.com +49 (0) 7158 173-0, 173-370 1-800-543-8390 +86 (0) 21-50 644131 For definitions of terms, see main catalog Subject to change without notice [181160]

eCl@ss 9.1: 27-44-01-02 ETIM 6.0: EC002062 BCC06YY_0.8_2017-05-29 1(1)