



1) Reference edge



## Display/Operation

Function indicator 1-5. Switch position: None

## Electrical connection

Connection type 1-5. Switch position: Screw terminal

## Electrical data

Continuous current 1-5. Switch position: 6 A  
 Rated operating voltage  $U_e$  1-5. Switch position: 250 V AC  
 Switching function mechanical Double-interrupting galvanically isolated One NO and one NC Dual changeover  
 Switching rate 1-5. Switch position: 300/min

## Environmental conditions

Ambient temperature -5...85 °C  
 IP rating per IEC 60529 IP67

## Functional safety

B10d (EN ISO 13849-1) BSE 30.0: 30 mil. switching cycles

## General data

Approval/Conformity CE  
 CCC  
 Basic standard IEC 60947-5-1  
 Operating principle 1-5. Switch position: mechanical

Version

Snap contact

## Material

Housing material Aluminum  
 Housing material, surface protection anodized  
 Material contacts 1-5. Switch position: Fine silver, gold plated  
 Plunger material 1-5. Switch position: Stainless steel (1.4034)

## Mechanical data

Approach direction longitudinal, parallel to attachment surface  
 Approach speed 1-5. Switch position: 40 m/min  
 Dimension 79 x 72 x 63 mm  
 Distance cam - reference edge 1-5. Switch position: 4.50...5.00 mm  
 Flange, feed-through None  
 Installation vertical  
 Life expectancy mechanical 1-5. Switch position: 30 mil. switching operations  
 Number of switching positions 5x Chisel  
 Plunger spacing 1st switch position 12 mm  
 Plunger style 1-5. Switch position: Chisel  
 Switch actuation force 1-5. Switch position: 20 N  
 Switching element 1-5. Switch position: BSE 30.0

## Range/Distance

Reproducibility 1-5. Switch position:  $\pm 0.002$  mm  
 Switch position spacing 12 mm  
 Specification of the MTTF value and the B10d value do not represent any binding quality and/or life expectancy guarantees.

Mechanical Cam Switches  
BNS 819-B05-D12-61-12-10  
Ordercode: BNS02AM

Note that the products listed here are not themselves safety components according to the Machine Directive 2006/42/EG Article 2 c. It is however possi-

ble to create corresponding structures with a high Performance Level per EN 13849-1 by means of two-channel utilization.

## Wiring Diagram

BSE 30.0

