

Switching points and analog output

Series AGK

Plastic thread

M18x1

M30x1.5

DC 18...30 V

Two switching points PNP

Sensing range adjustable



Design	Teach-in • M30x1.5	4...20 mA • M30x1.5	4...20 mA • M18x1
Dimensions			
Sensing range [mm]	250...2000	300...2500	200...1500
Output	2x		
ID-No.	P72005	P72011	P72010
Type	AGKU 2000 GIPP	AGKU 2500 GI	AGKU 1500 GI
Supply voltage [V]	19...30 DC	18...30 DC	18...30 DC
Current consumption [mA]	25	35	35
Load current [mA]	100	-	-
Current output [mA]	-	4...20	-
Load resistance R _L [Ω]	-	0...500	-
Linear deviation [%]	-	0.5	-
Ambient temperature [°C]	-	-15...+70	-
Temperature drift [%]	-	0.5	-
Protection [EN 60529]	-	IP 67	-
Housing material	PBTP		
Connection	M12 connector		
	<p>Mögliche Erfassung eines großen Objektes Possible detection of a large target</p> <p>Sichere Erfassung eines Objektes 100x100 mm Save detection of a target 100x100 mm</p>		
Accessories	Connecting type SLG 5-2 (Z01150), SLG 3-2 (Z01076)		