

KFX-ETC-320

Art.-Nr. 50117759

Lichtleiter, tastend

KFX-ETC-320

Part No. 50117759

fiber, reflective

Technische Daten

Lichtleiter Typ	koaxial
Betriebstemperatur	-55°C ... +70°C
Min. Biegeradius	R15
Außendurchmesser Lichtleiter	2x Ø1,25mm
Aktiver Durchmesser Faser	1x Ø0,5mm
	10x Ø0,25mm
Kleinstes erkennbares Teil	Ø0,05mm
Gesamtlänge	2019mm

Specifications

Fiber type	coaxial
Operating temperature	-55°C ... +70°C
Min. bending radius	R15
Fiber jacket diameter	2x Ø1.25mm
Active fiber diameter	1x Ø0.5mm
	10x Ø0.25mm
Smallest detectable object	Ø0.05mm
Total length	2019mm

Features




Typische Grenzreichweite für helle Objekte (weiß 90%) Typ. scanning range limit for light objects (white 90%)

LV463B	150mm
LV463	90mm
LV462	60mm
LV461	30mm

Maßzeichnung/Dimensioned drawing

Ø0.5 fiber optic
core x1
Ø0.25 fiber optic
core x10



Zubehör (separat erhältlich)/Accessories (available separately)

- KL-M03; 50117780
- KL-M03-1; 50117783