



MQDC2S-1215

▶ SINGLE-ENDED CORDSETS



Cordset Power and I/O
 Sealed 12-pin Euro-style QD
 to flying leads - High Flex
 Cable length: 5 m (15 ft)
 Part Number: 11421

SPECIFICATIONS

Number of Contacts	12
Number of Connectors	1
Cable Jacket Material	PVC
Cable Jacket Color	Black
Connector Body Material/Color	PVC Black
Outside Cable Diameter (mm)	7.5
Cordset Length (m)	4.57
Trunk Length (m)	No Trunk
Shield/No Shield	Shield
Shield Type	Open
Coupling Material/Color	Nickel Plated Brass
Maximum Temp. (°C)	105
Current Rating (A)	2.7
Minimum Temp. (°C)	-40
Voltage Rating (V)	250 V ac/300 V dc
IP Rating	IP67

Primary Connector Type	EURO
Primary Coupling Method	M12 Single Key
Primary Gender	Female
Primary Orientation	Straight
Primary Number of Conductors	12
Primary AWG	20, 24
Secondary Connector Type	Flying Leads
Feature: Hazardous Area	No
Oil/Grease Resistant	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America