










ID	Description	Characteristics	Outputs
Cable 530 032 	Dimensions: $3 \times 2 \times 0.14 \text{ mm}^2$ Cable Ø: 6 mm Material: PVC jacket; gray Operating temperature: $-10 \dots +80 \text{ }^\circ\text{C}$ Twisted pair shielded	Standard	Analog Start/Stop SSI
Cable 530 052 	Dimensions: $3 \times 2 \times 0.25 \text{ mm}^2$ Cable Ø: 6.4 mm Material: PUR jacket; orange Operating temperature: $-30 \dots +80 \text{ }^\circ\text{C}$ Twisted pair shielded	Halogen free Oil-resistant High flexible	Analog Start/Stop CAN SSI
Cable 530 116 	Dimensions: $4 \times 2 \times 0.25 \text{ mm}^2$ Cable Ø: 8 mm Material: PUR jacket; gray Operating temperature: $-30 \dots +90 \text{ }^\circ\text{C}$ Twisted pair shielded	Water proof wires Halogen free Flexible	Analog Start/Stop SSI
Cable 530 112 	Dimensions: $4 \times 2 \times 0.25 \text{ mm}^2$ Cable Ø: 7.6 mm Material: Teflon® jacket; black Operating temperature: $-100 \dots +180 \text{ }^\circ\text{C}$ Twisted pair shielded	Wide temperature range Chemical resistance	Analog Start/Stop CAN SSI
Cable 530 029 	Dimensions: $7 \times 0.14 \text{ mm}^2$ Cable Ø: 6.5 mm Material: TMPU jacket; orange Operating temperature: $-20 \dots +70 \text{ }^\circ\text{C}$	Additional EMC protection	CAN SSI
Cable 530 040 	Dimensions: $1 \times 2 \times 0.65 \text{ mm}^2$ $3 \times 1 \times 0.75 \text{ mm}^2$ Cable Ø: 8 mm Material: PVC jacket; petrol Operating temperature: $-30 \dots +80 \text{ }^\circ\text{C}$	Hybrid cable Profibus and power supply feed in	Profibus
Cable 530 109 	Dimensions: $1 \times 2 \times 0.64 \text{ mm}^2$ (AWG24) Cable Ø: 8 mm Material: PUR jacket; violett Operating temperature: $-30 \dots +70 \text{ }^\circ\text{C}$	High flexible	Profibus
Cable 530 125 	Dimensions: $2 \times 2 \times 0.75 \text{ mm}^2$ (AWG22/7) Cable Ø: 6.5 mm; 4 wires + shield Material: PUR jacket; green Operating temperature: $-40 \dots +70 \text{ }^\circ\text{C}$ Twisted pair shielded	High flexible	EtherCAT Ethernet/IP Profinet
Cable 530 108 	Dimensions: $3 \times 0.34 \text{ mm}^2$ Cable Ø: 4.9 mm; 3 wires + shield Material: PVC jacket; gray Operating temperature: $-30 \dots +80 \text{ }^\circ\text{C}$	Flexible	Power supply